

# Kinetic Research Group, LLC

## www.KRG-OPS.com

### ACTION WRENCH for TRG-22/42

Thank you for purchasing this exciting product from KRG! We believe that it will provide years of trouble free performance, and enhance your shooting experience. Careful consideration was given to design and material/finish selection. We are confident that the Action Wrench will be a quality product and a valuable addition to your rifle.

#### **Contents:**

-Action Wrench (Stressproof alloy steel with Mil-spec Manganese Phosphate "Parkerized" finish)

#### **Installation Instructions:**

(Note: A more fully illustrated version of these instructions, along with a video, will be posted on the website)

**Safety Warning:** Before you attempt any installation, make sure your rifle is unloaded. Also, before starting, remove the bolt and magazine from the rifle.

**Step 1:** Remove the cheek piece from the rear stock using a hex wrench (Metric size 5).

**Step 2:** Put the selector switch on "Fire", depress the bolt release, and insert the action wrench as if you were inserting the bolt into the action.

**Step 3:** Clamp the barrel in a vise and use a  $\frac{3}{4}$ " or 19mm socket wrench to turn the action off or onto the barrel. If installing a barrel, use a torque wrench to set the proper torque. Sako does not publish torque figures for barrel installation, however, 100ft/lbs seems to be a commonly accepted figure.

KRG is always looking for ways to improve its products, and ideas for new products. Please send any thoughts you might have to [info@krg-ops.com](mailto:info@krg-ops.com) with the subject "Future" or "Improvements."

If you have any problems with your new action wrench, please contact us so that we can fix the issue.

Thanks,  
KRG